



Medidas em Milímetros

Código	 Diâmetro Externo -mm-	 Diâmetro interno -mm-	 Espessura da Parede -mm-	 Pressão Máxima de Trabalho a 23°C -Bar-	 Comprimento da Bobina -metros-	 Raio Mínimo de Curvatura -mm-
407 MT	4,00	2,50	0,75	12	100	20
409 MT	4,40	2,90	0,75	10	100	20
410 MT	5,00	3,00	1,00	10	100	22
413 MT	6,00	4,00	1,00	10	100	25
423 MT	8,00	5,50	1,25	10	100	35
425 MT	8,00	5,00	1,50	12	100	30
427 MT	8,30	5,70	1,30	10	100	40
435 MT	10,0	7,00	1,50	10	50/100	40
449 MT	12,0	8,00	2,00	10	50	40
452 MT	14,0	10,0	2,00	9	50	60
454 MT	16,0	12,0	2,00	8	50	70
457 MT	18,0	13,0	2,50	8	50	90

Medidas em Polegadas

Código	 Diâmetro Externo -mm-	 Diâmetro interno -mm-	 Espessura da Parede -mm-	 Pressão Máxima de Trabalho a 23°C -Bar-	 Comprimento da Bobina -metros-	 Raio Mínimo de Curvatura -mm-
405 MT	3,20 (1/8")	1,60	0,80	12	100	15
411 MT	4,75 (3/16")	3,15	0,80	10	100	22
415 MT	6,35 (1/4")	4,35	1,00	10	100	25
431 MT	9,52 (3/8")	6,52	1,50	10	100	40
450 MT	12,7 (1/2")	8,70	2,00	10	50	50
459 MT	19,0 (3/4")	14,0	2,50	8	50	100

Cor Padrão

Azul

Outras Cores

Amarelo

Laranja

Natural

Cinza

Preto

Verde

Vermelho